

ProPostal 2000

Stamp Vending Device

ProPostal 2000 has been designed to move the standard process for postage payment - calculation of postage, sale of individual or sheets of stamps and envelope dispensing - from the counter onto a self-service device. Further functionalities can easily be added as options.

The vast benefits of ProPostal 2000 are immediately apparent: Counter employees can concentrate on more important tasks and consumers appreciate the fast, round-the-clock service. ProPostal 2000 is a reliable and indispensable sales channel not only in postal outlets but also in 3rd party locations.

The entire solution for postal automation is rounded off by a comprehensive software and services portfolio that allows carefree implementation and operation of your self-service network.

Highlights:

- Identifies weights
- Calculates postage
- Prints up to 2 different label types
- Issues receipts
- Convenient payment methods



■ Wincor Nixdorf's ProPostal 2000 supports postal organizations that are migrating basic postal transactions to a user-friendly and convenient self-service channel.

ProPostal 2000

TECHNICAL DATA

COINVALIDATOR

- Single feed
- Up to 16 denominations 5 tubes (recycling)
- 4 Coin hoppers, capacity: 350 coins/ each (depending on denomination)
- Shutter
- Escrow
- Locked cassette

BANKNOTEACCEPTOR

- Single feed (4 faces)
- Up to 3 denominations
- Locked cassette (capacity 400 banknotes)

CARD HANDLING

- Hybrid card reader (motorized)
- DIP reader
- DIP hybrid reader

PIN PAD

- Encrypted PIN Pad (EPP)

OPTIONAL PAYMENT MODULES

- Integration of country specific payment solutions

UPS

- (guarantees accomplishment of started transaction)

Published by
Wincor Nixdorf International GmbH
Heinz-Nixdorf-Ring 1
D-33106 Paderborn
Germany
Phone +49 (0) 52 51 / 6 93-33 01
Fax +49 (0) 52 51 / 6 93-59 18
info.banking@wincor-nixdorf.com
www.wincor-nixdorf.com

© Wincor Nixdorf International GmbH

ProCash® is a registered trademark of Wincor Nixdorf International GmbH. All rights, including rights created by patent grant or registration of a utility model or design, are reserved. Delivery subject to availability, subject to change for technical reasons.

Order No. **PDF-7600**

Printed in Germany, March 2006, S

PROPOSTAL 2000 WITH/WITHOUT SIDECAR

Housing	Free standing
Display	17" TFT colour monitor
Customer interface	Touch screen
CPU	Pentium 4 PC, 256 MB, 60 GB HD
Operating system	Windows XP
Multilingual support	yes
Scale	Integration in sidecar or basic system

DOOR OPEN ALARM

SINGLE STAMP PRINTER

- Thermal printer (200 dpi)
- Graphics, logos, alpha numerics
- 28 characters per line
- Printing speed: 10 cm/sec
- Printing width: 104 mm
- Min. Label length: 55 mm
- Label width: 111,5
- Roll max. diameter: 110 mm
- Full cutter
- Climate conditions:
Temperature: 5° – 40° C,
Humidity: 35 % - 80 %

STAMPSHEET PRINTER

- Thermal printer (200 dpi)
- Graphics, logos, alpha numerics
- 28 characters per line
- Printing speed: 10 cm/sec
- Printing width: 104 mm
- Min. label length: 55 mm
- Label width: 111,5
- Roll max. diameter: 110 mm
- Full cutter
- Climate conditions:
Temperature: 5° - 40° C,
Humidity: 35 % - 80 %

RECEIPTPRINTER

- Thermal printer (200 dpi)
- Graphics, logos, alpha numerics
- 28 characters per line
- Printing speed: 10 cm/sec
- Paper width: 60 mm
- Printing width: 56 mm
- Full cutter
- Approx. 1400 receipts/roll

SIDECAROPTIONS

- Scale module
- max. weight: 8100 gr.
- accuracy: 1 gr.
- stabilisation time: max. 2 sec
- Envelope dispenser
- Shipping document printer

POWER SUPPLY

- 120/230 V, 50/60 Hz

COMPLIANCE WITH STANDARDS



DIMENSIONS AND WEIGHT

	Height	Width	Depth	Weight
ProPostal 2000	1375 mm	692 mm (1125 mm)*	397 mm	approx. 90 kg*

*) depending on configuration