

ProConsult 2050

Multifunction information and transaction terminal for indoors and outdoors



Multifunction >

Through-the-wall installation >

Check scanner >

Design concept matches ATM family >

< Climate control unit

< Thermal or dot matrix printer

< Open hardware and software architectures

< Project-specific solutions



Technical Data

ProConsult 2050

Multifunction information
and transaction terminal
for indoors and outdoors

DISPLAY

- 12.1"
- Touchscreen or softkeys (stainless steel, Braille)
- Autoscaling

KEYBOARD

- Stainless-steel keyboards:
 - EPP
 - PIN pad
 - Alpha keyboard + trackball
 - Combo keyboard (alpha keyboard + EPP)
 - Multi keyboard (alpha keyboard + trackball + EPP)
- PIN shield (ZKA-/VISA-compliant)

CARD HANDLING

- Motorized hybrid card reader
- Card return after power failure

PRINTER

- Thermal or dot matrix technology
- One or two paper trays
- Paper cutter
- Document output: bundle (max. 10 documents) with retract function

DOCUMENT SCANNER

- Check scanner
 - MICR reading
 - Front and back scanning
- Printing function (endorsement)

USER GUIDANCE

- Optical indicators at all input/output modules

OPTIONS

- Barcode scanner
- Security locks
- Customizable color scheme
 - Single color
 - Multiple colors
 - RAL colors
 - Special colors
- Pull-out paper trays
- Other options on request

AUDIO

- Stereo loudspeakers
- Headset jack

OPERATING SYSTEM

- Windows XP

SYSTEM CONTROL

- Standard PC (Celeron or Pentium)

CONNECTION OPTIONS

- Ethernet LAN onboard
- Ethernet LAN card
- Token Ring LAN card
- X.25 WAN card
- ISDN card

POWER SUPPLY

- 220 – 240V~
- 50 Hz – 60 Hz

ENVIRONMENTAL CONDITIONS

Temperature range:
+5° C to +35° C (indoors)
+5° C to +55° C (outdoors without climate control unit)
-35° C to +55° C (outdoors with climate control unit)
Relative humidity:
5% to 85%

INSTALLATION

- Outdoors or indoors
- Rearload
- Through the wall
- Height-adjustable base

APPROVALS

